



Self-aligning ball bearings
d 5 – 25 mm



Cylindrical bore

Tapered bore

Principal dimensions	d	D	B	Basic load ratings		Fatigue load limit P_u	Speed ratings	Reference speed	Limiting speed	Mass	Designations	
				dynamic	static						Bearing with cylindrical bore	tapered bore
mm	mm	mm	mm	kN	kN	kN	r/min	r/min	r/min	kg		
5	19	6	6	2.51	0.48	0.025	63 000	45 000	0.009	135 TN9	-	-
6	19	6	6	2.51	0.48	0.025	70 000	45 000	0.009	126 TN9	-	-
7	22	7	7	2.65	0.56	0.029	63 000	40 000	0.014	127 TN9	-	-
8	22	7	7	2.65	0.56	0.029	60 000	40 000	0.014	108 TN9	-	-
9	26	8	8	3.90	0.82	0.043	60 000	38 000	0.022	129 TN9	-	-
10	30	9	9	5.53	1.18	0.061	56 000	36 000	0.034	1200 ETN9	-	-
	30	14	14	8.06	1.73	0.090	50 000	34 000	0.047	2200 ETN9	-	-
12	32	10	10	6.24	1.43	0.072	50 000	32 000	0.040	1201 ETN9	-	-
	32	14	14	8.52	1.90	0.098	45 000	30 000	0.053	2201 ETN9	-	-
	37	12	12	9.36	2.16	0.12	40 000	28 000	0.067	1301 ETN9	-	-
	37	17	17	11.7	2.70	0.14	38 000	28 000	0.095	2301	-	-
15	35	11	11	7.41	1.76	0.09	45 000	28 000	0.049	1202 ETN9	-	-
	35	14	14	8.71	2.04	0.11	38 000	26 000	0.060	2202 ETN9	-	-
	42	13	13	10.8	2.60	0.14	34 000	24 000	0.094	1302 ETN9	-	-
	42	17	17	11.9	2.90	0.15	32 000	24 000	0.12	2302	-	-
17	40	12	12	8.84	2.20	0.12	38 000	24 000	0.073	1203 ETN9	-	-
	40	16	16	10.6	2.55	0.14	34 000	24 000	0.088	2203 ETN9	-	-
	47	14	14	12.7	3.40	0.18	30 000	20 000	0.12	1303 ETN9	-	-
	47	19	19	14.6	3.55	0.19	30 000	22 000	0.16	2303	-	-
20	47	14	14	12.7	3.4	0.18	32 000	20 000	0.12	1204 ETN9	-	1204 EKTN9
	47	18	18	16.8	4.15	0.22	28 000	20 000	0.14	2204 ETN9	-	-
	52	15	15	14.3	4.75	0.21	26 000	18 000	0.16	1304 ETN9	-	-
	52	21	21	18.2	4.75	0.24	26 000	19 000	0.22	2304 TN	-	-
25	52	15	15	14.3	4	0.21	28 000	18 000	0.14	1205 ETN9	-	1205 EKTN9
	52	18	18	16.8	4.4	0.23	26 000	18 000	0.16	2205 ETN9	-	2205 EKTN9
	62	17	17	19	5.4	0.28	22 000	15 000	0.26	1305 ETN9	-	1305 EKTN9
	62	24	24	27	7.1	0.37	22 000	16 000	0.34	2305 ETN9	-	-

Dimensions	d	d ₂	D ₁	r _{1,2} min	Abutment and fillet dimensions		Calculation factors					
					d ₁ min	D ₁ max	r ₁ max	e	Y ₁	Y ₂	Y ₀	
mm	mm	mm	mm	mm	mm	mm	mm					
5	10.3	15.4	0.3	7.4	16.6	0.3	0.33	1.9	3	2		
6	10.3	15.4	0.3	8.4	16.6	0.3	0.33	1.9	3	2		
7	12.6	17.6	0.3	9.4	18.6	0.3	0.33	1.9	3	2		
8	12.6	17.6	0.3	10.4	18.6	0.3	0.33	1.9	3	2		
9	14.8	21.1	0.3	11.4	20.8	0.3	0.33	1.9	3	2		
10	16.7	24.4	0.6	14.2	25.8	0.6	0.33	1.9	3	1.8		
	15.3	24.3	0.6	14.2	25.8	0.6	0.54	1.15	1.8	1.3		
12	18.2	26.4	0.6	16.2	27.8	0.6	0.33	1.9	3	2		
	17.5	26.5	0.6	16.2	27.8	0.6	0.30	1.25	2.8	1.3		
	20	30.8	1	17.6	31.4	1	0.35	1.8	1.8	1.8		
	18.6	31	1	17.6	31.4	1	0.60	1.05	1.6	1.1		
15	21.2	29.6	0.6	19.2	30.8	0.6	0.33	1.9	3	2		
	20.9	30.2	0.6	19.2	30.8	0.6	0.43	1.5	2.3	1.6		
	23.2	35.5	1	20.6	36.4	1	0.31	2	3.1	2.2		
	23.2	35.2	1	20.6	36.4	1	0.52	1.2	1.9	1.3		
17	24	33.6	0.6	21.2	35.8	0.6	0.31	2	3.1	2.2		
	23.8	34.1	0.6	21.2	35.8	0.6	0.43	1.5	2.3	1.6		
	28.9	41	1	22.6	41.4	1	0.30	2.1	3.3	2.2		
	25.8	39.4	1	22.6	41.4	1	0.52	1.2	1.9	1.3		
20	28.9	41	1	25.6	41.4	1	0.30	2.1	3.3	2.2		
	27.4	41	1	25.6	41.4	1	0.40	1.6	2.4	1.5		
	33.3	45.6	1.1	27	45	1.1	0.28	2.2	3.5	2.5		
	28.8	43.7	1.1	27	45	1.1	0.52	1.2	1.9	1.3		
25	33.3	45.6	1	30.6	46.4	1	0.28	2.2	3.5	2.5		
	32.3	46.1	1.1	30.6	46.4	1.1	0.35	1.8	2.8	1.8		
	37.8	52.5	1.1	32	53	1.1	0.28	2.2	3.5	2.5		
	35.5	53.5	1.1	32	53	1.1	0.44	1.4	2.2	1.4		

