


Cylindrical Bore

Tapered Bore

Without an Oil Groove or Holes

Boundary Dimensions (mm)				Basic Load Ratings (N)			Limiting Speeds (min ⁻¹)		Bearing	
d	D	B	r min.	C _r	C _{0r}	C _r	C _{0r}	Grease	Oil	Cylindrical Bore
20	52	15	1.1	29 300	26 900	2 980	2 740	6 300	8 200	21304CDE4
25	52	18	1	37 500	37 000	3 850	3 800	7 100	9 000	22205CE4
	62	17	1.1	43 000	40 500	4 350	4 150	5 300	6 700	21305CDE4
30	62	20	1	50 000	50 000	5 100	5 100	6 000	7 500	22206CE4
	72	19	1.1	55 000	54 000	5 600	5 500	4 500	6 000	21306CDE4
35	72	23	1.1	69 000	71 000	7 050	7 200	5 300	6 700	22207CE4
	80	21	1.5	71 500	76 000	7 250	7 750	4 000	5 300	21307CDE4
40	80	23	1.1	113 000	99 500	11 500	10 100	6 700	8 500	*22208EAE4
	90	23	1.5	118 000	111 000	12 000	11 300	6 000	7 500	*21308EAE4
	90	33	1.5	170 000	153 000	17 300	15 600	5 300	6 700	*22308EAE4
45	85	23	1.1	118 000	111 000	12 000	11 300	6 000	7 500	*22209EAE4
	100	25	1.5	149 000	144 000	15 200	14 600	5 000	6 300	*21309EAE4
	100	36	1.5	207 000	195 000	21 100	19 900	4 500	5 600	*22309EAE4
50	90	23	1.1	124 000	119 000	12 600	12 100	5 600	7 100	*22210EAE4
	110	27	2	178 000	174 000	18 100	17 800	4 500	5 600	*21310EAE4
	110	40	2	246 000	234 000	25 100	23 900	4 300	5 300	*22310EAE4
55	100	25	1.5	149 000	144 000	15 200	14 600	5 300	6 700	*22211EAE4
	120	29	2	178 000	174 000	18 100	17 800	4 500	5 600	*21311EAE4
	120	43	2	292 000	292 000	29 800	29 800	3 800	4 800	*22311EAE4

Note (1) The suffix K represents bearings with tapered bores (taper 1 : 12).



Dynamic Equivalent Load

$$P = XF_1 + YF_2$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	Y ₃	0.67	Y ₂

Static Equivalent Load

$$P_0 = F_r + Y_0 F_a$$

The values of e , Y_2 , Y_3 , and Y_0 are given in the table below.

Numbers	Abutment and Fillet Dimensions (mm)				Constant	Axial Load Factors				Mass (kg)
	d_a		D_a			e	Y_2	Y_3	Y_0	
Tapered Bore ⁽¹⁾	min	max	max	min						approx.
21304CDKE4	27	28	45	42	1	0.31	3.2	2.1	2.1	0.17
22205CKE4	31	31	46	45	1	0.35	2.9	1.9	1.9	0.17
21305CDKE4	32	34	55	51	1	0.29	3.4	2.3	2.3	0.26
22206CKE4	36	37	56	54	1	0.33	3.1	2.1	2.0	0.27
21306CDKE4	37	40	65	59	1	0.28	3.6	2.4	2.3	0.39
22207CKE4	42	43	65	63	1	0.32	3.1	2.1	2.0	0.42
21307CDKE4	44	47	71	67	1.5	0.28	3.6	2.4	2.4	0.53
*22208EAKE4	47	49	73	70	1	0.28	3.6	2.4	2.4	0.50
*21308EAKE4	49	54	81	75	1.5	0.25	3.9	2.7	2.6	0.73
*22308EAKE4	49	52	81	77	1.5	0.35	2.8	1.9	1.9	0.98
*22209EAKE4	52	54	78	75	1	0.25	3.9	2.7	2.6	0.55
*21309EAKE4	54	65	91	89	1.5	0.23	4.3	2.9	2.8	0.96
*22309EAKE4	54	59	91	86	1.5	0.34	2.9	2.0	1.9	1.34
*22210EAKE4	57	60	83	81	1	0.24	4.3	2.9	2.8	0.61
*21310EAKE4	60	72	100	98	2	0.23	4.4	3.0	2.9	1.21
*22310EAKE4	60	64	100	93	2	0.35	2.8	1.9	1.9	1.78
*22211EAKE4	64	65	91	89	1.5	0.23	4.3	2.9	2.8	0.81
*21311EAKE4	65	72	110	98	2	0.23	4.4	3.0	2.9	1.58
*22311EAKE4	65	73	110	103	2	0.34	2.9	2.0	1.9	2.3

Remarks

1. The bearings denoted by an asterisk (*) are NSK HPS bearings and an oil groove and holes are standard for them.
2. When making a selection of the recommended fit (Tolerance of Shaft) on Page A84 of the NSK Rolling Bearings catalog, in case of NSK HPS bearings, the conditions are different.
3. The segmentations are: Light Loads ($\leq 0.05 C_r$), Normal Loads (0.05 to $0.10 C_r$), and Heavy Loads ($> 0.10 C_r$).

For the dimensions of adapters and withdrawal sleeves, refer to Pages B358 – B359, and B366.