

d 75 – 95 mm

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No.	(Refer.) Dimension series to ISO355	(Refer.) Mass (kg)
d	D	T	B	C	$r_{\min.}$	$r_{1\min.}$	C_r	C_{0r}	Grease lub.	Oil lub.			
75	105	20	20	16	1	1	73.6	123	3 300	4 400	32915JR	2BC	0.526
	115	25	25	19	1.5	1.5	110	169	3 100	4 200	32015JR	4CC	0.930
	115	31	31	25.5	1.5	1.5	141	225	3 200	4 200	33015JR	2CE	1.16
	125	37	37	29	2	1.5	186	280	3 000	4 000	33115JR	3DE	1.84
	130	27.25	25	22	2	1.5	142	181	2 900	3 900	30215JR	4DB	1.42
	130	33.25	31	27	2	1.5	174	234	2 900	3 900	32215JR	4DC	1.77
	130	41	41	31	2	1.5	212	310	2 900	3 900	33215JR	3EE	2.26
	160	40	37	26	3	2.5	222	266	2 100	2 900	30315DR	—	3.48
	160	40	37	31	3	2.5	260	311	2 500	3 300	30315JR	2GB	3.65
	160	58	55	45	3	2.5	363	481	2 500	3 300	32315JR	2GD	5.41
	110	20	20	16	1	1	76.1	131	3 100	4 200	32916JR	2BC	0.556
	125	29	29	22	1.5	1.5	147	225	2 900	3 900	32016JR	3CC	1.32
80	125	36	36	29.5	1.5	1.5	173	288	2 900	3 900	33016JR	2CE	1.63
	130	37	37	29	2	1.5	191	294	2 800	3 800	33116JR	3DE	1.93
	140	28.25	26	22	2.5	2	161	202	2 700	3 600	30216JR	3EB	1.72
	140	35.25	33	28	2.5	2	203	271	2 700	3 600	32216JR	3EC	2.17
	140	46	46	35	2.5	2	250	371	2 700	3 600	33216JR	3EE	2.99
	170	42.5	39	27	3	2.5	236	282	2 000	2 800	30316DJR	7GB	4.12
	170	42.5	39	33	3	2.5	294	355	2 300	3 100	30316JR	2GB	4.46
	170	61.5	58	48	3	2.5	383	503	2 300	3 100	32316JR	2GD	6.31
	120	23	23	18	1.5	1.5	97.1	165	2 900	3 900	32917JR	2BC	0.794
	130	29	29	22	1.5	1.5	150	234	2 800	3 700	32017JR	4CC	1.38
	130	36	36	29.5	1.5	1.5	177	300	2 800	3 700	33017JR	2CE	1.72
	140	41	41	32	2.5	2	224	346	2 600	3 500	33117JR	3DE	2.43
85	150	30.5	28	24	2.5	2	182	231	2 500	3 400	30217JR	3EB	2.17
	150	38.5	36	30	2.5	2	232	315	2 500	3 400	32217JR	3EC	2.80
	150	49	49	37	2.5	2	294	439	2 500	3 400	33217JR	3EE	3.63
	180	44.5	41	28	4	3	263	317	1 900	2 600	30317DJR	7GB	4.81
	180	44.5	41	34	4	3	316	384	2 200	2 900	30317JR	2GB	5.15
	180	63.5	60	49	4	3	439	587	2 200	3 000	32317JR	2GD	7.42
	125	23	23	18	1.5	1.5	101	175	2 800	3 700	32918JR	2BC	0.834
	140	32	32	24	2	1.5	178	276	2 600	3 500	32018JR	3CC	1.80
	140	39	39	32.5	2	1.5	221	367	2 600	3 400	33018JR	2CE	2.22
	150	45	45	35	2.5	2	258	413	2 500	3 300	33118JR	3DE	3.13
	160	32.5	30	26	2.5	2	204	261	2 400	3 200	30218JR	3FB	2.65
	160	42.5	40	34	2.5	2	263	362	2 400	3 200	32218JR	3FC	3.47
90	190	46.5	43	30	4	3	282	336	1 700	2 400	30318DR	—	5.60
	190	46.5	43	36	4	3	345	420	2 100	2 700	30318JR	2GB	6.04
	190	67.5	64	53	4	3	461	614	2 100	2 800	32318JR	2GD	8.61
	145	32	32	24	2	1.5	182	287	2 500	3 300	32019JR	4CC	1.88
	145	39	39	32.5	2	1.5	226	382	2 500	3 300	33019JR	2CE	2.31
	160	49	49	38	2.5	2	304	473	2 300	3 100	33119JR	3EE	3.89
	170	34.5	32	27	3	2.5	231	299	2 200	3 000	30219JR	3FB	3.20
	170	45.5	43	37	3	2.5	311	439	2 200	3 000	32219JR	3FC	4.34
	170	58	58	44	3	2.5	374	582	2 200	2 900	33219JR	3FE	5.66
	200	49.5	45	32	4	3	319	391	1 700	2 300	30319DJR	7GB	6.68
	200	49.5	45	38	4	3	372	455	2 000	2 600	30319JR	2GB	6.96
	200	71.5	67	55	4	3	517	695	2 000	2 600	32319JR	2GD	10.1