

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 15

SDS No.: 153497 V007.0

Revision: 06.06.2016

printing date: 05.07.2016

Replaces version from: 14.12.2015

LOCTITE 574

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 574

Contains:

Maleic acid

Acetic acid, 2-phenylhydrazide

N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer
H317 May cause an allergic skin reaction

Category 1

2.2. Label elements

Label elements (CLP):



Signal word: Warning

MSDS-No.: 153497 LOCTITE 574 Page 2 of 15

V007.0

Hazard statement:	H317 May cause an allergic skin reaction.
Precautionary statement:	***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***
Precautionary statement: Prevention	P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

MSDS-No.: 153497 LOCTITE 574 Page 3 of 15

V007.0

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Decan-1-ol 112-30-1	203-956-9 01-2119480407-35	5-< 10 %	Eye Irrit. 2 H319 Aquatic Chronic 3 H412
Cumene hydroperoxide 80-15-9	201-254-7	0,1-< 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1-< 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
Maleic acid 110-16-7	203-742-5 01-2119488705-25	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335
1,4-Naphthalenedione 130-15-4	204-977-6	0,01-< 0,1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide) 123-26-2	204-613-6 01-2119978265-26	0,1-< 1 %	Skin Sens. 1B H317 Aquatic Chronic 4 H413

For full text of the ${\bf H}$ - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

MSDS-No.: 153497 LOCTITE 574 Page 4 of 15

V007.0

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eve contact

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Do not expose to direct heat.

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

MSDS-No.: 153497 LOCTITE 574 Page 5 of 15

V007.0

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at $8-21^{\circ}$ C ($46.4-69.8^{\circ}$ F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Anaerobic Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE]		4	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUSTI		2,4	Time Weighted Average (TWA):		IR_OEL

MSDS-No.: 153497 LOCTITE 574 Page 6 of 15

V007.0

$\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value	Value			Remarks
		F	mg/l	ppm	mg/kg	others	
Decan-1-ol	aqua			**	0 0	0,022 mg/L	
112-30-1	(freshwater)						
Decan-1-ol	sediment				0,13 mg/kg		
112-30-1	(freshwater)						
Decan-1-ol	aqua (marine					0,0022 mg/L	
112-30-1	water)						
Decan-1-ol	sediment				0,013		
112-30-1	(marine water)				mg/kg		
Decan-1-ol	soil				0,13 mg/kg		
112-30-1							
Decan-1-ol	sewage					0,4 mg/L	
112-30-1	treatment plant (STP)						
.alpha.,.alphaDimethylbenzyl	aqua					0,0031 mg/L	
hydroperoxide 80-15-9	(freshwater)						
.alpha.,.alphaDimethylbenzyl	aqua (marine					0,00031 mg/L	
hydroperoxide	water)					0,00031 mg/L	
80-15-9	,						
.alpha.,.alphaDimethylbenzyl	aqua					0,031 mg/L	
hydroperoxide	(intermittent					3	
80-15-9	releases)						
.alpha.,.alphaDimethylbenzyl	Sewage					0,35 mg/L	
hydroperoxide	treatment plant						
80-15-9							
.alpha.,.alphaDimethylbenzyl	sediment				0,023		
hydroperoxide	(freshwater)				mg/kg		
80-15-9							
.alpha.,.alphaDimethylbenzyl	sediment				0,0023		
hydroperoxide 80-15-9	(marine water)				mg/kg		
.alpha.,.alphaDimethylbenzyl	soil				0,0029		
hydroperoxide					mg/kg		
80-15-9							
Maleic acid	aqua					0,1 mg/L	
110-16-7	(freshwater)						
Maleic acid	aqua					0,4281 mg/L	
110-16-7	(intermittent						
26.1	releases)				0.224		
Maleic acid	sediment				0,334		
110-16-7	(freshwater)		1		mg/kg	14.6/I	
Maleic acid 110-16-7	sewage treatment plant					44,6 mg/L	
110-10-7	(STP)						
Maleic acid	aqua (marine					0,01 mg/L	
110-16-7	water)						
Maleic acid	sediment				0,0334	_	
110-16-7	(marine water)				mg/kg		
Maleic acid	soil				0,0415		
110-16-7					mg/kg		

MSDS-No.: 153497 LOCTITE 574 Page 7 of 15

V007.0

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - local effects		0,55 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - local effects		0,04 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - systemic effects		58 mg/kg bw/day	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - systemic effects		3,3 mg/kg bw/day	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - systemic effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - systemic effects		3 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

MSDS-No.: 153497 LOCTITE 574 Page 8 of 15

V007.0

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance paste orange
Odor mild

Odour threshold No data available / Not applicable

pH Not applicable Initial boiling point > 150 °C (> 302 °F) Flash point > 93,3 °C (> 199.94 °F)

Decomposition temperature No data available / Not applicable

Vapour pressure 6,6700000 mbar (27,0 °C (80.6 °F))

Vapour pressure < 300 mbar

(50 °C (122 °F))

Density 1,15 g/cm3 ()

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solidification temperature

Melting point

No data available / Not applicable

Auto-ignition temperature

Explosive limits

No data available / Not applicable

Partition coefficient: n-octanol/water

No data available / Not applicable

Evaporation rate Not applicable

Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

9.2. Other information

Ignition temperature Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids. Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

MSDS-No.: 153497 LOCTITE 574 Page 9 of 15

V007.0

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Prolonged or repeated contact may cause eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Decan-1-ol	LD50	> 5.000 mg/kg	oral		rat	Henkel Method
112-30-1						
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	
80-15-9						
Maleic acid	LD50	708 mg/kg	oral		rat	
110-16-7						
1,4-Naphthalenedione	LD50	190 mg/kg	oral		rat	
130-15-4						
N,N'-Ethane-1,2-	LD50	> 2.000 mg/kg	oral			
diylbis(12-						
hydroxyoctadecan-1-						
amide)						
123-26-2						

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Decan-1-ol	Acute	5,1 mg/l	aerosol			Expert judgement
112-30-1	toxicity	_				
	estimate					
	(ATE)					
Decan-1-ol	LC50	4 mg/l		2 h	mouse	
112-30-1						

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Decan-1-ol	LD50	> 5.000 mg/kg	dermal		rat	EPA OPPTS 870.1200 (Acute
112-30-1						Dermal Toxicity)
Cumene hydroperoxide	LD50	1.200 - 1.520	dermal			
80-15-9		mg/kg				
Maleic acid	LD50	1.560 mg/kg	dermal		rabbit	
110-16-7						

MSDS-No.: 153497 LOCTITE 574 Page 10 of 15

V007.0

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Decan-1-ol	slightly irritating	4 h	human	Patch Test
112-30-1				
Decan-1-ol	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute
112-30-1				Dermal Irritation / Corrosion)
Cumene hydroperoxide	corrosive		rabbit	Draize Test
80-15-9				
Maleic acid	irritating	24 h	human	Patch Test
110-16-7				

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Decan-1-ol 112-30-1	highly irritating		rabbit	Draize Test
Maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Maleic acid 110-16-7	sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Decan-1-ol 112-30-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Henkel Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	
Maleic acid 110-16-7	negative	bacterial reverse mutation assay (e.g Ames test)	no data		Ames Test
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity:

Hazardous components	Result	Species	Sex	Exposure	Route of	Method
CAS-No.				timeFrequenc	application	
				y of treatment		
Maleic acid	not carcinogenic	rat	male/female	2 y	oral: feed	OECD Guideline 451
110-16-7				daily		(Carcinogenicity Studies)

MSDS-No.: 153497 LOCTITE 574 Page 11 of 15

V007.0

Reproductive toxicity:

Hazardous substances	Result / Classification	Species	Exposure	Species	Method
CAS-No.			time		
Maleic acid	NOAEL $F1 = 150 \text{ mg/kg}$	Two	min. 80 d	rat	OECD Guideline 416 (Two-
110-16-7	NOAEL $F2 = 55 \text{ mg/kg}$	generation			Generation Reproduction
		study			Toxicity Study)
		oral: gavage			

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	
Maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

SECTION 12: Ecological information

General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

MSDS-No.: 153497 LOCTITE 574 Page 12 of 15

V007.0

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Decan-1-ol 112-30-1	LC50	2,2 - 2,5 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
	NOEC	0,26 mg/l	Fish	33 d	Pimephales promelas	OECD 210 Guideline (fish early lite stage
Decan-1-ol 112-30-1	EC50	2,9 mg/l	Daphnia	48 h	Daphnia magna	toxicity test) OECD Guideline 202 (Daphnia sp. Acute
Decan-1-ol 112-30-1	EC50	1,5 mg/l	Algae	72 h	Desmodesmus subspicatus	Immobilisation Test) QSAR (Quantitative Structure Activity
	EC10	0,7 mg/l	Algae	72 h	Desmodesmus subspicatus	Relationship) QSAR (Quantitative Structure Activity
Decan-1-ol 112-30-1	EC0	10.000 mg/l	Bacteria	30 min	Pseudomonas putida	Relationship) DIN 38412, part 27 (Bacterial oxygen consumption test)
Decan-1-ol 112-30-1	NOEC	0,11 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna,
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	Reproduction Test) OECD Guideline 203 (Fish, Acute
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test)
Cumene hydroperoxide	EC10	70 mg/l	Bacteria	30 min		ininoidon Test)
80-15-9 Maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Maleic acid 110-16-7	EC50	42,81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth
N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	LL50	> 10 mg/l	Fish	96 h	Oncorhynchus mykiss	Inhibition Test) OECD Guideline 203 (Fish, Acute
123-26-2 N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide) 123-26-2	EL50	> 10 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) 123-26-2	EC50	> 100 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
120 20 2	NOEC	100 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

12.2. Persistence and degradability

Persistence and Biodegradability: The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

MSDS-No.: 153497 LOCTITE 574 Page 13 of 15

V007.0

Decan-1-ol 112-30-1	readily biodegradable	aerobic	88 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F
N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) 123-26-2	Not readily biodegradable.	aerobic	22 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil $\,$

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential:

No data available for the product.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Decan-1-ol 112-30-1 Decan-1-ol 112-30-1	4,5	20		calculated	25 °C	QSAR (Quantitative Structure Activity Relationship) OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9 Cumene hydroperoxide 80-15-9	2,16	9,1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74					
Maleic acid 110-16-7	-1,3				20 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71					
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide) 123-26-2	5,86					OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
Maleic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
110-16-7	Bioaccumulative (vPvB) criteria.
N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1-amide)	Bioaccumulative (vPvB) criteria.
123-26-2	

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

MSDS-No.: 153497 LOCTITE 574 Page 14 of 15

V007.0

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture VOC content $$<5\ \%$$

VOC content (2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 153497 LOCTITE 574 Page 15 of 15

V007.0

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Xi - Irritant



Risk phrases:

R43 May cause sensitisation by skin contact.

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S37 Wear suitable gloves.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

Maleic acid

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.