


d (45) ~ (55) mm



Boundary dimensions (mm)					Basic load ratings (kN)		Fatigue load limit (kN) C _u	Limiting speeds (min ⁻¹) Grease Oil lub.		Bearing No.			Mounting dimensions (mm)										(Refer.) Mass NU (N) (kg)		
d	D	B	r _{min.}	r _{1min.}	C _r	C _{0r}				NU	NJ	NUP	N	NF	d _a min.	d _b min.	d _c min.	d _d min.	d _a max.	D _b max.	r _a min.	r _b max.			
45	85	19	1.1	1.1	57.6	46.9	6.70	7 700	9 200	—	—	—	N209	NF209	51.5	—	—	61	78.5	78.5	77	1	1	(0.427)	
	85	19	1.1	1.1	78.9	66.4	9.05	7 600	9 200	NU209R	NJ209R	NUP209R	—	—	51.5	51.5	54	57	61	78.5	—	1	1	0.439	
	85	23	1.1	1.1	76.6	67.8	9.60	6 900	9 200	NU2209	NJ2209	NUP2209	—	—	51.5	51.5	54	57	61	78.5	—	1	1	0.536	
	85	23	1.1	1.1	95.1	84.6	11.2	6 900	9 200	NU2209R	NJ2209R	NUP2209R	—	—	51.5	51.5	54	57	61	78.5	—	1	1	0.536	
	85	30.2	1.1	1.1	103	99.0	13.3	6 100	9 200	NU3209	—	—	—	—	51.5	51.5	54	57	—	78.5	—	1	1	0.770	
	100	25	1.5	1.5	98.5	77.5	11.3	6 200	8 300	—	—	—	N309	NF309	53	—	—	66	92	92	89	1.5	1.5	(0.865)	
	100	25	1.5	1.5	122	98.3	13.5	6 100	8 200	NU309R	NJ309R	NUP309R	—	—	53	53	57	60	66	92	—	1.5	1.5	0.909	
	100	36	1.5	1.5	124	113	14.3	5 500	8 300	NU2309	NJ2309	NUP2309	—	—	53	53	57	60	66	92	—	1.5	1.5	1.25	
	100	36	1.5	1.5	172	153	23.0	5 400	8 200	NU2309R	NJ2309R	NUP2309R	—	—	53	53	57	60	66	92	—	1.5	1.5	1.32	
	100	39.7	1.5	1.5	164	149	22.6	5 500	8 300	NU3309	—	—	—	—	53	53	57	60	—	92	—	1.5	1.5	1.59	
120	29	2	2	134	112	13.8	5 400	7 200	NU409	NJ409	NUP409	N409	NF409	54	54	63	66	74	111	111	102	2	2	1.64	
50	80	16	1	0.6	42.2	36.8	4.80	8 400	9 900	NU1010	—	—	—	—	55	54	57	59	—	75	—	1	0.6	0.306	
	90	20	1.1	1.1	60.3	51.0	7.30	7 100	8 500	—	—	—	N210	NF210	56.5	—	—	67	83.5	83.5	82	1	1	(0.479)	
	90	20	1.1	1.1	82.5	71.9	9.85	7 100	8 500	NU210R	NJ210R	NUP210R	—	—	56.5	56.5	58	62	67	83.5	—	1	1	0.497	
	90	23	1.1	1.1	80.3	73.6	10.4	6 400	8 500	NU2210	NJ2210	NUP2210	—	—	56.5	56.5	58	62	67	83.5	—	1	1	0.580	
	90	23	1.1	1.1	99.5	91.5	12.1	6 400	8 500	NU2210R	NJ2210R	NUP2210R	—	—	56.5	56.5	58	62	67	83.5	—	1	1	0.580	
	90	30.2	1.1	1.1	108	108	14.5	5 700	8 500	NU3210	—	—	—	—	56.5	56.5	58	62	—	83.5	—	1	1	0.829	
	110	27	2	2	109	93.4	11.7	5 600	7 500	—	—	—	N310	NF310	59	—	—	73	101	101	98	2	2	(1.15)	
	110	27	2	2	138	113	16.0	5 500	7 400	NU310R	NJ310R	NUP310R	—	—	59	59	63	67	73	101	—	2	2	1.15	
	110	40	2	2	151	142	20.1	5 000	7 500	NU2310	NJ2310	NUP2310	—	—	59	59	63	67	73	101	—	2	2	1.69	
	110	40	2	2	203	187	28.6	4 900	7 400	NU2310R	NJ2310R	NUP2310R	—	—	59	59	63	67	73	101	—	2	2	1.76	
110	44.4	2	2	195	183	27.3	5 000	7 500	NU3310	—	—	—	—	59	59	63	67	—	101	—	2	2	2.14		
130	31	2.1	2.1	161	136	17.4	4 900	6 600	NU410	NJ410	NUP410	N410	NF410	61	61	69	73	81	119	119	112	2	2	2.01	
55	90	18	1.1	1	47.1	43.8	5.75	7 600	8 900	NU1011	—	—	—	—	61.5	60	63	66	—	83.5	—	1	1	0.445	
	100	21	1.5	1.1	72.5	62.3	8.30	6 400	7 700	—	—	—	N211	NF211	63	—	—	—	73	92	93.5	91	1.5	1	(0.633)
	100	21	1.5	1.1	108	98.7	14.2	6 400	7 700	NU211R	NJ211R	NUP211R	—	—	63	61.5	65	68	73	92	—	1.5	1	0.650	
	100	25	1.5	1.1	94.2	87.2	11.6	5 800	7 700	NU2211	NJ2211	NUP2211	—	—	63	61.5	65	68	73	92	—	1.5	1	0.780	

[Remarks] 1) Standard cage types used for the above bearings are shown in Table 1 earlier in this section. Please note that basic load ratings and limiting speeds shown above indicate the value applicable to machined cage. Consult JTEKT about bearings with pressed cage, since they may be different from bearings with machined cage in values above.

2) Bearing numbers of NU and NJ type bearings with mounted thrust collar (refer to specification table shown after this specification table) are NUJ and NH.