



Needle roller bearings

sealed, without
inner ring

Series RNA 49..RS,
RNA 49...2RS



RNA 49..RS



RNA 49...2RS

103 066

103 067

Dimension table · Dimensions in mm

Shaft diam- eter	Series		Dimensions					Basic load ratings		Limiting speed $n_{l \text{ grease}} \approx$ min ⁻¹
	RNA 49..RS Sealed on one side Designation	RNA 49...2RS Sealed on both sides Designation	Mass g	F_w	D	C	r_s min.	dyn. C N	stat. C ₀ N	
14	RNA 4900 RS	RNA 4900.2RS	16	14	22	13	0,3	6 800	6 900	13 000
16	RNA 4901 RS	RNA 4901.2RS	18	16	24	13	0,3	7 600	8 300	12 000
20	RNA 4902 RS	RNA 4902.2RS	21,5	20	28	13	0,3	8 600	10 300	10 000
22	RNA 4903 RS	RNA 4903.2RS	23	22	30	13	0,3	8 800	11 000	9 000
25	RNA 4904 RS	RNA 4904.2RS	56	25	37	17	0,3	17 300	19 900	7 500
30	RNA 4905 RS	RNA 4905.2RS	60	30	42	17	0,3	19 300	24 200	6 500
35	RNA 4906 RS	RNA 4906.2RS	69	35	47	17	0,3	21 100	28 500	5 500
42	RNA 4907 RS	RNA 4907.2RS	107	42	55	20	0,6	26 500	39 500	4 800
48	RNA 4908 RS	RNA 4908.2RS	154	48	62	22	0,6	36 000	53 000	4 200
52	RNA 4909 RS	RNA 4909.2RS	157	52	68	22	0,6	38 000	59 000	3 900
58	RNA 4910 RS	RNA 4910.2RS	160	58	72	22	0,6	40 000	64 000	3 500