

Performance you can trust

Penetrating Spray

Powerful penetrating fluid, with molybdenum disulphide, in an aerosol.

A powerful jet application of lubricant that penetrates to give quick and effective release of corroded threaded fasteners or similar seized components. It contains molybdenum disulphide, to aid disassembly, and corrosion inhibitors to provide a protective film against further corrosive attack.

Features

- Excellent penetration of rust, scale, grease, oil etc...
- Molybdenum disulphide aids dismantling
- Protective film provides short term corrosion protection
- Fast acting performance

Directions for Use

- Ideally remove any excessive oil, grease or dirt contamination.
- Shake can, and coat thoroughly from approx 10-30 cm (4-12 inches)
- In severe cases a second coating a few mins later may prove beneficial
- Allow time for penetration to occur before attempting to release
- Test compatibility with painted or coated surfaces and rubbers prior to application.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Penetrating Spray

Appearance	Pale amber liquid
Solids	Molybdenum disulphide
Penetrant	Blend of mineral oil and hydrocarbon solvents
Propellant	CO ₂ (Carbon dioxide)
Storage	Storage area should be: out of direct sunlight. Storage temperature should be kept below 50°C.
Pack sizes – Part Codes	300 ml – p/c

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.