Technical Data

Performance you can trust



FOODLUBE® Universal 2



Food grade, multipurpose, extreme pressure (EP) grease fortified with PTFE

Product Overview

ROCOL[®] FOODLUBE Universal 2 is a white, nontoxic lubricant designed for the effective lubrication and protection of ball, roller and plain bearings, slides and bushes operating in food, pharmaceutical and other clean environments.

FOODLUBE Universal 2 is an excellent all round NLGI No.2 grease offering excellent water wash-off resistance and corrosion protection necessary for lubricants used in food, pharmaceutical and other clean environments.

Also available as NLGI No. 0 & 000 versions – see FOODLUBE Universal 0 & FOODLUBE Universal 000.

Features and Benefits

- FOODLUBE Universal 2 offers an excellent wide temperature resistance of -50°C to +160°C.
- It exhibits outstanding EP performance with a 4 ball weld load of 620 kg.
- FOODLUBE Universal 2 is highly resistant to water wash-off and offers excellent corrosion protection.
- FOODLUBE Universal 2 has excellent oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- FOODLUBE Universal 2 is truly versatile, reducing the lubricant inventory and stock levels required on site.

Directions for Storage and Use

- FOODLUBE Universal 2 can be applied manually, by grease gun, keg pump or by other methods suitable for an NLGI No. 2 grease.
- FOODLUBE Universal 2 is compatible with other soap thickened greases. However, for best results the previous lubricant should be removed prior to application.
- The storage temperature should be controlled between +1 and +40°C
- Shelf life is 3 years from date of manufacture.

Specifications

- FOODLUBE Universal 2 does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FOODLUBE Universal 2 is manufactured from only FDA listed ingredients:
 - FDA Group 21 CFR 178.3570
- FOODLUBE Universal 2 is NSF registered:
 - NSF H1 registered 121603
- ISO 21469 certified

Pack Sizes

Pack Size	Part Code
380g	15231
4kg	15236
18kg	15234

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of IT W Ltd



ate No. FM 12448



BS EN ISO 1400

e No. FMS 67596



te No. OHS 78173





Performance you can trust





FOODLUBE® Universal 2

Food grade, multipurpose, extreme pressure (EP) grease fortified with PTFE

Property	Test Method	Result
Appearance	Visual	White tenacious grease
NLGI No.	IP50 – ASTM D217	2
Base Type	N/A	Polyalphaolefin
Base Fluid Viscosity at 40°C	IP71 – ASTM D445	47cSt
Base Fluid Viscosity at 100°C	IP71 – ASTM D445	8cSt
Thickener	N/A	Aluminium complex soap
Solids	N/A	White, non-toxic solids/PTFE
Temperature Range	N/A	-50°C to +160°C
4-Ball Weld Load	IP239 – ASTM D2596	620kg
SKF ROF Bearing Life	N/A	1100 hours
Corrosion Test - Emcor	IP 220	0:0
Copper Corrosion Test	IP112 – ASTM D130	1b
Water Washout Test	IP215 – ASTM D1264	<2%
Drop Point	IP132 – ASTM D566	>230°C

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website <u>www.rocol.com</u> or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Issue: 2 Date: 01-11

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *IT* W Ltd











BS EN ISO 9001 Certificate No. FM 12448 BS EN ISO 14001 OHSAS 18001 Certificate No. EMS 67596 Certificate No. OHS 78173