

TUFGEAR SPRAY

Page: 1

Compilation date: 13/07/2011

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TUFGEAR SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Open gear lubricant.

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House
	Swillington
	Leeds
	West Yorkshire
	LS26 8BS
	ENGLAND
Tel:	+44 (0) 113 232 2700
Fax:	+44 (0) 113 232 2740
Email:	customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; -: R67; -: R52/53

Most important adverse effects: Extremely flammable. Vapours may cause drowsiness and dizziness. Harmful to

aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Extremely flammable.



Risk phrases:	R12: Extremely flammable.	
	R67: Vapours may cause drowsiness and dizziness.	
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the	
	aquatic environment.	
Safety phrases:	S16: Keep away from sources of ignition - No smoking.	

TUFGEAR SPRAY

 S23: Do not breathe spray.

 S51: Use only in well-ventilated areas.

 S35: This material and its container must be disposed of in a safe way.

 Precautionary phrases:

 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

EINECS	CAS	CHIP Classification	CLP Classification	Percent
270-704-2	68476-85-7	F+: R12	-	50-70%

ISOPARAFFINIC HYDROCARBON

292-458-5 90622-56-3 F: R11; Xn: R65; Xi: R38; -: R67; N: R51/53	-	10-30%
---	---	--------

ACETONE

200-662-2 67-64-1 F: R11; Xi: R36; -: R66; -: R67	-	1-10%
---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Page: 2

TUFGEAR SPRAY

Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: Do not use water. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Extremely flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. 5.3. Advice for fire-fighters Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Section 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. 6.2. Environmental precautions Environmental precautions: Do not discharge into drains or rivers. 6.3. Methods and material for containment and cleaning up Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. 6.4. Reference to other sections Section 7: Handling and storage 7.1. Precautions for safe handling Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. 7.2. Conditions for safe storage, including any incompatibilities Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition. Suitable packaging: Must only be kept in original packaging. 7.3. Specific end use(s) Section 8: Exposure controls/personal protection

TUFGEAR SPRAY

-

8.1. Control parameters

Hazardous ingredients:

HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)

1200 mg/m3

Workplace exposure limits:

-	-		-	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000ppm 1750mg/m3	1250ppm 2180mg/m3	-	-

-

Respirable dust

-

ISOPARAFFINIC HYDROCARBON

UK

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
equipment are not a source of ignition.Respiratory protection:Respiratory protection not normally required.Hand protection:Protective gloves.Eye protection:Safety glasses with side-shields.Skin protection:Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol	
Colour:	Black	
Odour:	Characteristic odour	
Evaporation rate:	Fast	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Not miscible	
Viscosity:	Non-viscous	
Boiling point/range°C:	< 0 Melting point/range°C	: <-130
Flammability limits %: lower:	1.8 upper	9.4
Flash point°C:	< -100 Autoflammability°C	: > 200
Vapour pressure:	> 210 Relative density	: <1

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

TUFGEAR SPRAY

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Highly volatile. Heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

TUFGEAR SPRAY

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.
	Safety data sheet prepared in accordance with Commission Directive 2008/47/EC of 8
	April 2008 amending, for the purposes of adapting to technical progress, Council
	Directive 75/324/EEC relating to aerosol dispensers
Phrases used in s.2 and 3:	R11: Highly flammable.
	R12: Extremely flammable.
	R36: Irritating to eyes.

TUFGEAR SPRAY

R38: Irritating to skin.

	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic	
	environment.	
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the	
	aquatic environment.	
	R65: Harmful: may cause lung damage if swallowed.	
	R66: Repeated exposure may cause skin dryness or cracking.	
	R67: Vapours may cause drowsiness and dizziness.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive	
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	

Page: 7