Technical Data



Performance you can trust

RTD® Spray Metal Cutting Lubricant Spray

RTD[®] Spray is an aerosol applied metal cutting lubricant consisting of a concentrate of extreme pressure additives. RTD[®] Spray applies an economical film metal cutting fluid directly to the cutting zone, particularly in areas where access is difficult.

Features

- Superb cutting performance.
- Suitable for all ferrous metals.
- Ideal for reaming, tapping, drilling and general workshop operations.
- Fast and convenient application.

Directions for Use

Shake well before use and spray directly onto workpiece or tool from a distance of 15 - 30 cm. Test compatibility with painted or coated surfaces, plastics and rubbers prior to application.

Ensure adequate ventilation.

Appearance	Brown liquid
Solvent	Pentane
Propellant	Propane/Butane
Shell 4-Ball	
Weld Load	>800kg
Load-Wear Index	179kg
Tapping Torque (316 Stainless Steel)	11.2NM
Silicones	None
Storage	Storage temperature should be kept below
	50°C. Storage area should be out of direct
	sunlight
Pack Sizes – Part Codes	400ml - 53011

Date: Jan-09

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of TW Ltd









The information in this publication is based on our experience and reports from customers.

There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.