

Performance you can trust

## RTD<sup>®</sup> COMPOUND Hand Applied Metal Cutting Lubricant

RTD<sup>®</sup> Compound is a soft paste for use in reaming, tapping and drilling and other metal cutting operations. RTD<sup>®</sup> Compound is suitable for all metals including hardened steels, nimonics and titaniums. Containing extreme pressure additives, RTD<sup>®</sup> Compound significantly reduces friction giving superb cutting performance.

### Features

- Extends tool life.
- Improves surface finish.
- Allows increases removal rates.
- Reduces production costs.

### Directions for Use

Apply directly to the tool or workpiece by brush, or by dipping tool into the compound.

<b>Appearance</b>	Brown paste
<b>Odour</b>	Mild pine
<b>Shell 4-Ball</b>	
<b>Weld Load (Neat)</b>	>800 kg
<b>Weld Load (5% in Oil)</b>	315 kg
<b>Storage</b>	Store at normal ambient temperature (5 to 30°C)
<b>Pack Sizes – Part Codes</b>	50g - 53020 500g - 53023 5 kg - 53026 18 kg - 53028 185 kg - 53029

Date: Jan-09

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E customer-service@rocol.com  
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.